



X.Robot Manual

www.xinorbis.com

www.maximumoctopus.com

xinorbis@maximumoctopus.com

www.twitter.com/maximumoctopus

freshney.wordpress.com

Introduction

XinorbisRobot (x.robot) is a command-line version of Xinorbis (the awesome, and powerful, storage analysis tool). It was designed to be a simple-to-use companion to its big brother, the Windows GUI version. If you have any suggestions on how to improve this software or identify any bugs, then please email me at the address on the credits page.

The software is capable of giving you a quick analysis of the distribution and contents of a folder. For desktop users and network administrators it should make finding unwanted content much easier.

Once a folder or drive has been scanned then you have the ability to create many reports from that data.

Xinorbis is a powerful program so please read (and print if possible) the whole of this manual; you'll find lots of interesting information on features that allow you to make the most of the application.

X.Robot can create its own data and, or if Xinorbis is installed, can update the Folder History database if required.

Conventions

When dealing with file sizes Xinorbis uses the following conventions;

| | |
|------------------|---|
| 1 kilobyte (1K) | = 1024 bytes |
| 1 megabyte (1MB) | = 1048576 bytes (1024 x 1024) |
| 1 gigabyte (1GB) | = 1073741824 bytes (1024 x 1024 x 1024) |
| 1 terabyte (1TB) | = 1099511627776 bytes (1024 x 1024 x 1024 x 1024) |

Not all applications follow this convention but as well as being the most commonly used throughout the industry it's also how Windows reports file sizes.

It's worth noting that hard disk manufacturers tend to use a slightly different method when reporting hard disk sizes;

| | |
|------------------|---|
| 1 gigabyte (1GB) | = 1000000000 bytes (1000 x 1000 x 1000) |
| 1 terabyte (1TB) | = 1000000000000 bytes (1000 x 1000 x 1000 x 1000) |

Installation

X.Robot doesn't need installing in the normal sense. Either add the folder where X.Robot is located to the "path" environmental variable or refer to it by its full path in batch files (etc.).

Ideally Xinorbis and X.Robot should be on the same PC. The database can be anywhere, but a local install is best (if possible) as it will increase write/read performance. Writing to a local database (sqlite or odbc) is also kinder to the network.

There should be ten files in the root of the X.Robot folder. The 9 ".txt" files contain associations that Xinorbis uses to decide which category a file belongs to. Each file contains a list of file extensions (without leading .) one per line. Feel free to edit these!

If you're planning on using X.Robot with Xinorbis (by doing all the scanning automatically or through batch files, for example) then I suggest putting both of them in the same folder. This will allow them to share config settings (eg. odbc connection string) and will make things a bit easier. It'll also stop them getting lonely.

Command Line Parameters

The first parameter is always the path to scan

```
x.robot.exe <folder>
```

If X.Robot is executed with just this one parameter then it will output a simple summary of the scan to the console.

All comments and suggestions are gratefully received; please email them to me at xinorbis@maximumoctopus.com

Miscellaneous Commands

```
*nothing*
```

Outputs version and basic "about" information" (web address and email etc.)

```
/? or /h
```

Simple help, and a few stats.

```
/o
```

Disables status output.

```
/p
```

Show scan and processing progress

```
/u
```

Open this document.

Database Access

X.Robot can update a Xinorbis database if required to do so (this is probably its most powerful and useful feature). Use X.Robot to update the database (e.g. automatically through a batch file or scheduled task) and then use Xinorbis to view reports, graphs etc.

```
/odbc
```

Updates an ODBC compliant database with all file and folder information.

X.Robot will expect a custom.ini file with a "connectionstring" parameter in the same format as Xinorbis.

Ideally Xinorbis and X.Robot should live in the same folder; they'll be much happier and can share config information.

connectionstrings are database-vooodoo, for more help on creating them see this excellent website: <https://www.connectionstrings.com/>.

```
/sqlite
```

Updates an SQLite 3 database with all file/folder details.

X.Robot will read the config.ini file and use the same database as Xinorbis. If no config.ini file is present then the default path will be used. Depending on which version of Windows is installed:

```
C:\documents and settings\\xinorbis\folderhistory\database\xinorbis.db
```

```
C:\users\\xinorbis\folderhistory\database\xinorbis.db
```

```
/updatescanhistory
```

Updates the Xinorbis Scan History. Only useful if you use Xinorbis on the same PC as X.Robot (this is recommended!).

The command below will scan "somefolder" and update the Xinorbis database via ODBC and update the Xinorbis scan history:

```
x.robot somefolder /odbc /updatescanhistory
```

If somefolder contains spaces then use quotes around the folder path:

```
x.robot "some folder" /odbc /updatescanhistory
```

Optimisations

```
/nouser
```

Don't gather user details; this will improve scan performance, however it will mean that reports will not be able to show user usage statistics.

```
/noprocess
```

If you only plan on producing file lists, or updating a database, then use this option as it will stop Xinorbis from unnecessarily processing file data.

Report Output

If no report options are selected then a basic summary of the directory scan will be output to the console.

The configuration options in the braces {110} are OPTIONAL. The defaults are specified where appropriate.

The majority of options are either on or off, toggling an option is simply a matter of replacing the letters (a, b, c etc.) with either;

0 to disable the option

1 to enable the option

Where an option has many settings then this is specified separately.

If no output file name is specified then X.Robot will save the file to either:

The folder specified in the custom.ini file:

```
[X.Robot]
DataPath = <folder>
```

Or if the above cannot be found, or is blank:

```
[Main]
DataPath = <folder>
```

If DataPath is blank then X.Robot will use:

```
<xinorbis data>\x.robot\Reports\<report>\xcom_yyyymmdd_hhmmss.xxx
```

typically: c:\users\user\xinorbis\x.robot\Reports\...

If custom.ini cannot be found then, X.Robot will use:

```
<X.Robot folder>\system\Reports\<report>\xcom_yyyymmdd_hhmmss.xxx
```

Generate CSV report

Outputs a CSV file to the path specified in <file name>.

Items in { } are optional, <file name> parameter is optional. Default shows the values that will be used if no parameters are specified.

Usage: /CSV{abc};<file name>

Default: /CSV{110};<output folder>\xcom_yyyymmdd_hhmmss.csv

option a; 0 - category output only
1 - full file list (default)

option b; 0 - Don't add "heading row"
1 - Add "heading row" (default)

option c; 0 - File sizes in most convenient format (1MB, 400bytes etc.)
1 - All file sizes in bytes
2 - All file sizes in kilobytes
3 - All file sizes in megabytes

If a file name is not specified then it will be saved using the rules on **Page 4 – Report Output**.

Example:

/CSV{1}

Create only a list of files in the scan

/CSV{10}

Create only a list of files in the scan and don't add a heading row.

Generate HTML report

Outputs an HTML report to the path specified in <file name>.

Items in { } are optional, <file name> parameter is optional. Default shows the values that will be used if no parameters are specified.

Usage: /HTM{abcdefghijkl};<file name>

Default: /HTM{111111111120};<output folder>\xcom_yyyymmdd_hhmmss.htm

| | | |
|-----------|---|----------------|
| option a; | graphs on (1 default) or off (0) | |
| option b; | include File Attributes section | (default is 1) |
| option c; | include Category section | (default is 1) |
| option d; | include Directories section | (default is 1) |
| option e; | include Magnitude section | (default is 1) |
| option f; | include File Extension list section | (default is 1) |
| option g; | include Null Files section | (default is 1) |
| option h; | include File Dates section | (default is 1) |
| option i; | include Top 50 section | (default is 1) |
| option j; | include Users section | (default is 1) |
| option k; | 0 - report is 800 pixels wide | |
| | 1 - report is 1024 pixels wide | |
| | 2 - report is 1280 pixels wide | (default) |
| option l; | 0 - File sizes in most convenient format (1MB, 400bytes etc.) | |
| | 1 - All file sizes in bytes | |
| | 2 - All file sizes in kilobytes | |

If a file name is not specified then it will be saved using the rules on **Page 4 – Report Output**.

Generate a simple summary of findings

Outputs a summary to the console.

Usage: /SUM

Default: /SUM

Only outputs data to the console.

Generate an ASCII text report

Outputs an ASCII text report file to the path specified in <file name>.

Items in { } are optional, <file name> parameter is optional. Default shows the values that will be used if no parameters are specified.

Usage: /TXT{abcdefghij};<file name>

Default: /TXT{1111111111};<output folder>\xcom_yyyymmdd_hhmmss.txt

| | | |
|-----------|-------------------------------------|----------------|
| option a; | UNUSED | |
| option b; | include File Attributes section | (default is 1) |
| option c; | include Category section | (default is 1) |
| option d; | include Directories section | (default is 1) |
| option e; | include Magnitude section | (default is 1) |
| option f; | include File Extension list section | (default is 1) |
| option g; | include Null Files section | (default is 1) |
| option h; | include File Dates section | (default is 1) |
| option i; | include Top 50 section | (default is 1) |
| option j; | include Users section | (default is 1) |

If a file name is not specified then it will be saved using the rules on **Page 4 – Report Output**.

Generate an XML report

Outputs an XML 1.0 compliant report file to the path specified in <file name>. Report can either be a complete list of files along with properties, or, category usage data.

Items in { } are optional, <file name> parameter is optional. Default shows the values that will be used if no parameters are specified.

Usage: /XML{abcdefghijkl};<file name>

Default: /XML{0111111111};<output folder>\xcom_yyyymmdd_hhmmss.xml

| | | |
|-----------|-------------------------------------|----------------|
| option a; | file list (1) or summary of results | (default is 0) |
| option b; | include File Attributes section | (default is 1) |
| option c; | include Category section | (default is 1) |
| option d; | include Directories section | (default is 1) |
| option e; | include Magnitude section | (default is 1) |
| option f; | include File Extension list section | (default is 1) |
| option g; | include Null Files section | (default is 1) |
| option h; | include File Dates section | (default is 1) |
| option i; | include Top 50 section | (default is 1) |
| option j; | include Users section | (default is 1) |

If a file name is not specified then it will be saved using the rules on **Page 4 – Report Output**.

Generate an XML file list report

<file name> parameter is optional. Default shows the values that will be used if no parameters are specified.

Usage: /XFL;<file name>

Default: /XFL

Outputs an XML 1.0 compliant report to the path specified in <file name>.

If a file name is not specified then it will be saved using the rules on **Page 4 – Report Output**.

Dynamic file name generation

For use in all options that take a file name as a parameter.

| | |
|--------|--|
| \$XD | The drive where X.Robot was run from |
| \$XF | The folder where X.Robot was run from |
| \$PC | The name (network) of the PC X.Robot is executed on |
| \$User | The name of the user that executed X.Robot |
| \$yyyy | Current year (e.g. 2009) |
| \$YY | Last two digits of current year (e.g. 08) |
| \$mm | Current month (01 for January, 02 for February etc.) |
| \$MM | Current month as short word (Jan, Feb, Mar, Apr etc.) |
| \$dd | Current day (01 through 28, 29, 30 or 31 depending on month) |
| \$DD | Current day as short word (Mon, Tue, Wed etc.) |
| \$Th | Hour part of the current time (00 - 23) |
| \$Tm | Minute part of the current time (00 - 59) |
| \$Ts | Second part of the current time (00 - 59) |

Examples of usage;

Current date in yyyymmdd format;

```
/TXT;c:\xinorbis\%$yyyy%$mm%$dd_dailyscan.txt
```

Store files in individual folders for month and year;

```
/TXT;c:\scan\%$yyyy%\$mm%\$dd_dailyscan.txt
```

XML Report Structure

Xinorbis outputs fully v1.0 compliant XML.

Structure for XML file list ;

```
<xinorbisfilelist>
  <file>
    <name>          File name
    <path>          Full file path
    <sizewords>     Size represented in most convenient format; 1MB, 500K etc.
    <sizebytes>     Size in bytes
    <sizeondiskwords> Used disk space in the most convenient format; 1MB, 500K etc.
    <sizeondiskbytes> Actual used disk space in bytes
    <owner>         File owner
    <datecreated>   Date file created in DD/MM/YYYY format
    <datemodified>  Date file modified in DD/MM/YYYY format
    <dateaccessed>  Date file was last accessed in DD/MM/YYYY format
    <category>      File category (1- programs etc.)
    <directory>     1 if folder, 0 if file.
    <readonly>      1 if file is read only
    <hidden>        1 if file is hidden
    <system>        1 if file is system file
    <archive>       1 if file is archive
  </file>
</xinorbisfilelist>
```

Structure for XML report output

```
<xinorbisreport>
<information>
  <directory>      analysed path
  <date>           date of analysis
  <numberoffiles>  number of files included in analysis
  <numberofdirectories> number of folder in analysis
  <sizeoffiles>    total size of the files analysed
  <diskspacefree>  disk space available on target drive
  <diskspacemax>  disk space total on target drive
  <sectorspercluster> number of sectors per cluster
  <bytespersector> number of bytes per sector
  <freeclusters>  free clusters on hard disk
  <totalclusters> total clusters on hard disk
  <volumename>    volume name of hard disk
  <serialnumber>  hard disk serial number
  <filesystem>    file system type (FAT32, NTFS etc.)
</information>
<categorylist>
  <category name=""> one section for each of the 10 file categories
  <numberoffiles>   number of files belonging to relevant category
  <numberoffilesaspercent> number of files as percentage of total analysed
  <sizeoffiles>     size of files analysed, belonging to relevant category
  <sizeoffilesaspercent> size of files as percentage of total analysed, relevant category
</categorylist>
<dirlist>
  <dir name="">    one section for each dir analysed
  <numberoffiles>  number of files in analysed folder
  <numberoffilesaspercent> number of files as percentage of total analysed
  <sizeoffiles>    combined size of files
```

```
        <sizeoffilesaspercent> combined size of files, as percentage of total analysed
    </dir>
</dirlist>

<magnitudelist>
    <magnitude name=""> one section for each magnitude category
        <numberoffiles> number of files in analysed folder
        <numberoffilesaspercent> number of files as percentage of total analysed
        <sizeoffiles> combined size of files
        <sizeoffilesaspercent> combined size of files, as percentage of total analysed
    </magnitude>
</magnitudelist>

<extensiondata>
    <extensioncategory name=""> one section for each extension category
        <numberoffiles> number of files in analysed folder
        <numberoffilesaspercent> number of files as percentage of total analysed
        <sizeoffiles> combined size of files
        <sizeoffilesaspercent> combined size of files, as percentage of total analysed

        <extension name=""> one section for extension within this category that has more
            than one file associated with it

            <numberoffiles> number of files in analysed folder
            <numberoffilesaspercent> number of files as percentage of total analysed
            <sizeoffiles> combined size of files
            <sizeoffilesaspercent> combined size of files, as percentage of total analysed
        </extension>
    </extensioncategory>
</extensiondata>

<top50largest>
    <top50large size="">path to file</top50large>
</top50largest>

<top50smallest>
    <top50small size="">path to file</top50small>
</top50smallest>

<>nullfiles>
    <>nullfile name="">path to</nullfile>
</nullfiles>

</xinorbisreport>
```

If you need any help with the XML output please don't hesitate to contact me.

Credits

| | |
|------------------------------|---|
| Programming | Paul Alan Freshney |
| Development Cats | Rutherford and Freeman |
| Database Engine | SQLite (www.sqlite.org) |
| ZIP Compression | TZipMaster (www.delphizip.org) |
| Application Icon/Logo | Sören Bockhoop |
| French Translation | Christian Perronnet |
| German Translation | Marcus Barkhahn |
| Hungarian Translation | Zsolt Brechler |
| Russian Translation | kopejkin |
| Italian Translation | Victor |
| Thanks to | Monpelaud, Dave Mahadevan, Vit, Damiaan Peeters, Mike Dutch, Robert Pallot, Peter Garrety, Fred de Vries, Glyn Selwyn, Tom Grimes, Freddie Botha and Rod. And <i>everyone</i> who has sent me feedback. Please keep it coming! |
| Lines of source code | 11422 |

www.harddiskanalyser.com

www.xinorbis.com

www.maximumoctopus.com

xinorbis@maximumoctopus.com